

AMENDMENTS TO THE CLAIMS

The listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A method for producing gas from a subterranean formation containing a coal seam, comprising the steps of:

drilling at least one substantially vertical well bore into the subterranean formation, which intersects the coal seam, ~~and~~

fracturing the coal seam using a hydrajetting tool at a pressure less than a fracture pressure of the subterranean formation to produce at least one pair of opposed bi-wing fractures formed by erosion of the subterranean formation substantially along a plane of maximum stress[.], and

performing an additional fracturing subsequent to the step of fracturing the coal seam using the hydrajetting tool.

2. (Original) The method of claim 1, further comprising the step of casing the at least one substantially vertical well bore.

3. (Original) The method of claim 2, further comprising the step of perforating the casing with the hydrajetting tool.

4. (Currently Amended) The method of claim 1, further comprising the step of removing water, ~~if present~~, from the coal seam of the subterranean formation.

5. (Original) The method of claim 1, further comprising the step of inserting logging equipment into the at least one substantially vertical well bore.

6. (Original) The method of claim 1, wherein during the fracturing step the hydrajetting tool produces a plurality of pairs of opposed bi-wing fractures.

7. (Cancelled)

8. (Currently Amended) A method for producing gas from a subterranean formation containing a coal seam, comprising the steps of:

drilling at least one substantially vertical well bore into the subterranean formation, which intersects the coal seam,

fracturing the coal seam using a hydrajetting tool at a pressure less than a fracture pressure of the subterranean formation to produce at least one pair of opposed bi-wing fractures substantially along a plane of maximum stress,

drilling at least one horizontal well bore into the coal seam, ~~and~~

fracturing the coal seam along the horizontal well bore using a hydrajetting tool at a pressure less than the fracture pressure of the subterranean formation to produce at least one pair of opposed bi-wing fractures formed by erosion of the subterranean formation[[]], and

performing an additional fracturing subsequent to the step of fracturing the coal seam using the hydrajetting tool along the horizontal well bore.

9. (Original) The method of claim 8, further comprising the step of casing the at least one substantially vertical well bore and the at least one horizontal well bore.

10. (Original) The method of claim 9, further comprising the step of perforating the casing with the hydrajetting tool.

11. (Currently Amended) The method of claim 8, further comprising the step of removing water, ~~if present~~, from the coal seam of the subterranean formation.

12. (Original) The method of claim 8, further comprising the step of inserting logging equipment into the at least one substantially vertical well bore.

13. (Original) The method of claim 8, wherein during the fracturing steps the hydrajetting tool produces a plurality of pairs of opposed bi-wing fractures.

14. (Cancelled)

15. (Currently Amended) A method for producing gas from a subterranean formation containing a coal seam, comprising the steps of:

drilling at least one substantially vertical well bore intersecting the coal seam,

logging the subterranean formation by inserting logging equipment into the at least one substantially vertical well bore,

casing the at least one substantially vertical well bore, ~~and~~

fracturing the coal seam along the substantially vertical well bore using a
hydrajetting tool at a pressure less than a fracture pressure of the subterranean formation to
produce at least one pair of opposed bi-wing fractures formed by erosion of the subterranean
formation substantially along a plane of maximum stress[[]], and
performing an additional fracturing subsequent to the step of fracturing the coal
seam using the hydrajetting tool.

16. (Original) The method of claim 15, further comprising the step of perforating the casing with the hydrajetting tool.

17. (Currently Amended) The method of claim 15, further comprising the step of removing water, ~~if present,~~ from the coal seam of the subterranean formation.

18. (Original) The method of claim 15, wherein during the fracturing step the hydrajetting tool produces a plurality of pairs of opposed bi-wing fractures.

19. (Cancelled)

20. (Currently Amended) A method for producing gas from a subterranean formation containing a coal seam, comprising the steps of:

drilling at least one substantially vertical well bore intersecting the coal seam,
logging the subterranean formation by inserting logging equipment into the at
least one substantially vertical well bore,

casing the at least one substantially vertical well bore,

drilling a plurality of substantially horizontal well bores disposed substantially
within the coal seam and exiting from the at least one substantially vertical well bore, wherein
the plurality of substantially horizontal well bores is spaced to maximize interference between
the substantially horizontal well bores,

casing the plurality of substantially horizontal well bores,

fracturing the coal seam along the substantially vertical well bore using a
hydrajetting tool at a pressure less than a fracture pressure of the subterranean formation to
produce at least one pair of opposed bi-wing fractures formed by erosion of the subterranean
formation substantially along a plane of maximum stress, and

fracturing the coal seam along the plurality of substantially horizontal well bores using a hydrajetting tool at a pressure less than the fracture pressure of the subterranean formation to produce a plurality of fractures formed by erosion of the subterranean formation, wherein the plurality of fractures is spaced to maximize interference between fractures and wherein the plurality of fractures enhances the production of gas from the coal seam of the subterranean formation[[]], and

performing an additional fracturing subsequent to the step of fracturing the coal seam using the hydrajetting tool along the plurality of substantially horizontal well bores..

21. (Original) The method of claim 20, further comprising the step of perforating the casing with the hydrajetting tool.

22. (Currently Amended) The method of claim 20, further comprising the step of removing water, ~~if present~~, from the coal seam of the subterranean formation.

23. (Original) The method of claim 20, wherein during the fracturing steps the hydrajetting tool produces a plurality of pairs of opposed bi-wing fractures.

24. (Cancelled)

25. (New) The method of claim 1 wherein the step of performing the additional fracturing is performed using a hydrajetting tool.

26. (New) The method of claim 8 wherein the step of performing the additional fracturing is performed using a hydrajetting tool.

27. (New) The method of claim 15 wherein the step of performing the additional fracturing is performed using a hydrajetting tool.

28. (New) The method of claim 20 wherein the step of performing the additional fracturing is performed using a hydrajetting tool.